



* For loads over 30000 kg, request ball with Ø 80

Stage diameter [mm]	Thrust at 125 bar [ton]
265	68.9
236	54.7
210	43.3
187	34.3
165	26.7
145	20.6
126	15.6

Cylinder Description	Ø Stages [mm]									Stroke [mm]	E [mm]	R [mm]	Ø Ball [mm]	Capacity [Lt]	Weight [Kg]
	I	II	III	IV	V	VI	VII	VIII	IX						
B DWR 7/1410/ 300	265	236	210	187	165	145	126			1410	455	266	68	45.7	167
B DWR 7/1550/ 300										1550	475	282		50.2	175
B DWR 7/1690/ 300										1690	495	298		54.6	187
B DWR 7/1830/ 300										1830	515	315		59.1	195
B DWR 7/1970/ 300										1970	535	332		63.5	200
B DWR 7/2110/ 300										2110	555	349		68.0	209
B DWR 7/2390/ 300										2390	595	384		76.9	226
B DWR 7/2800/ 300										2800	655	439		89.2	250
B DWR 7/4235/ 300										4235	910	681	80*	135	363
B DWR 7/4515/ 300										4515	960	730	80*	144	380
B DWR 7/5075/ 300										5075	1060	828	80*	162	417

ACCESSORIES

Cradle		Brackets		Turn adapters	
CUL#CQ			SU#AE	RSN#90ADXBD0	RSN#00ADXAD1