FRONT END CYLINDER

TYPE : MFC


SERIE : Ø 145

CYL.TYPE

MFC 145.4.5100 - Ic.0267

For Tipping Weight See Advices Below

Technical Characteristics



Cylinder stages

Ø Stage	Ø045	Ø060	Ø076	Ø092	Ø108	Ø069	Ø088	Ø107	Ø126	Ø145	Ø165	Ø167	Ø187	Ø210	Ø236	Ø265
Thrust at 200 Bar [Tons]		5.55	200	(exe	255	(eeees	12.20	18.00	24.90	33.00	(0.0.0)	(4.5.5)	255	00000	1.1.1	0.00
Stages of cylinder							0	0	0	0						

Specifications

Stages number		04
Cylinder Stroke	[mm]	5100
Cylinder weight only	[Kgs]	261
Working volume	[Ltrs]	56.1
Max Working pressure	[Bar]	200

Technical information

□ Oil	: See oil specification sheet	
☐ Tipping weight	: Net weight body + Payload	
☐ Fitted centres [*]	: Closed centres plus 20 mm pull out	

Brackets and Accessories

Chassis bracket [2 Units x cylinder]	SIL#MHH	12.20 [Kgs] x 2 =		
Lifting bracket right hand	SSL#PGH	10.30 [Kgs] x 1 =		
Lifting bracket left hand	SSL#PHH	10.30 [Kgs] x 1 =		
Chassis brackets mounting kit	KFSI#001			
Lifting bracket mounting kit	KFSS#002			

Recommendation

- ☐ This Binotto cylinder is designed as a lifting device only
- ☐ It must not be used as a structural member or be subject to side loads
- ☐ Pump flow in consultation with Binotto engineering department

Advices

All our cylinders are manufactured to suit the particular application in the differing world markets/climate. Should you require details of the exact lifting capacity of the cylinder that has been selected for your application/vehicle then please contact our technical department who will be only pleased to explain or advise.

BINOTTO SRL

BINOTTO IS CONSTANTLY ENGAGED IN IMPROVING ITS PRODUCTS AND THEREFORE RESERVES THE RIGHT TO MODIFY WITHOUT ANY NOTICE CHARACTERISTICS SHOWN VIA DIVISIONE JULIA, 7/18 - 36031 DUEVILLE [VI] ITALY • TEL. 0039.0444.593290 - FAX. 0039.0444.593357 • E-MAIL. INFO@BINOTTO.COM

Edit.: 04 • 2006 Rev.: 02 • 2009

Rev.: 02 • 2009 Date: 20.07.2009

Pag.: MFC 145.4.5100_04